

IG-253B

The **IG-253B** is the "big brother" of the IG-244B. This box can be used for testing small device such as cellphones, routers and small set ups.

Although the **IG-253B** is bigger than the IG-244B, it has a light weight that allows the user to take it to anywhere he may need for demonstrations.

The **IG-253B** is designed for testing any wireless transmission such as: Wi-Fi, Bluetooth, RFID, 3G, WLAN, GPS and Wimax. It may also be used for cell-site testing, RF resistor testing and two-way radio testing.

Features

- Fast, reliable EMI/RFI testing and verification, while providing 100% effective shielding of 90dBm minimum attenuation tested as per as
- MIL-STD-285D up to 6GHz
- High performance construction of Aluminum and copper EMC shielding with ROHs compliant welding and RAL 9010 STD coating.
- User Friendly, compact design and light weight.
- Manual operation with top loading, toggle opened door, latch locking action.
- Shielding tested under lab conditions with signal generator by spectrum analyzer and conforming antenna. Manufacturer's C.O.T. and test results included.
- For small UUT's
- Custom-made product adaptable to any application..



Accessories

- Double 68X68 Honey-comb air vent
- Exhaust fan
- 4 SMA connectors
- Filtered terminal 220VAC max 16 Amp
- AC power supply plug in + cord cable
- 1 Outlet 120VAC/15A,
- Filtered terminal 50VDC max 20 Amp
- DC Plug in
- RF absorbent foam liner
- Double lip RF sealing
- Grounding Point

Optional Accessories

- Anechoic absorber lining for the interior surface
- Custom IO's pane.
- Waveguide for optic fibers
- RF shielded observation window
- Internal illumination
- Additional in-port/out-port systems
- Extra custom-made requirements

IG-253B

Technical Data

IG-253B	
Dimensions - External	Dimensions - Internal
Width: 32cm	Width: 29cm
Depth: 51cm	Depth: 40cm
Hight: 24cm	Hight: 20cm
Material	Opening System
Body: Aluminum	Manual operation
Door: Aluminum	Top loading
Frames: SAE 1020	Toggle opened door
Brackets: SAE 1020	Latch locking action
Fan: Rubber, Sponge and Plastic	RF sealing set
Gaskets: Rubber, Sponge and Plastic	
Electric system	Air vents
220 VAC max 16 Amp	EMI shielded windows (honeycomb)
1 outlet power strip 220 VAC	AC fan 68x68 - 40 CFM, magnetic - bearing, silence
External power cable 220 VAC + plug	
100VDC filter 20amp with easy-to-use plug in.	
IO's plate	Internal RF absorber
Filtered SMA x4	24 db , internal surfaces covering with RF absorber foam
Attenuation level	Quality
0.1GHz - 1.0GHz > 90dB	Testing according to MIL-STD 285
1.0GHz - 3.0GHz > 90dB	A C.O.A will be attached to each box.
3.0GHz - 6.0GHz > 90dB	Final Attenuation level will set as per as the weak chosen connector
	Warranty - one year from delivering



IG-253B

Technical Drawing

IG-253B

