


IG-262E

The **IG-262E** design with modular structure, for assemble at the lab location.

The **IG-262E** has been developed for testing large set-ups, and provides high attenuation level..

The chamber design for testing any wireless transmission such as: Wi-Fi, Bluetooth, RFID, 3G, WLAN, GPS and WiMAX.

It may also be used for cell-site testing, RF resistor testing and two-way radio testing.



Features

- Fast, reliable EMI/RFI testing and verification, while providing 100% effective shielding of 120dBm minimum attenuation tested as per as
- MIL-STD-285D up to 6GHz
- High performance construction of SAE 1020 and copper EMC shielding with ROHs compliant welding and RAL 9010 STD coating.
- Manual operation with front loading, big handle opened door.
- Shielding tested under lab conditions with signal generator by spectrum analyzer and conforming antenna. Manufacturer's C.O.T. and test results included.
- For large UUT's
- Custom-made product adaptable to any application..

Accessories

- Double Honey-comb vent windows 260X260 mm
- Exhaust fan
- 4 SMA connectors
- Filtered terminal 220VAC max 32 Amp
- AC power supply plug in + cord cable
- 4 Outlet 120VAC/15A
- Filtered terminal 50VDC max 20 Amp
- DC Plug in
- RF absorbent foam liner
- Double lip RF sealing
- Grounding Point
- Internal illumination

Optional Accessories

- Anechoic absorber lining for the interior surface
- Custom IO's panel with any filtered connectors you may need.
- Waveguide for optic fibers
- RF shielded observation window
- Additional in-port/out-port systems
- Extra custom-made requirement

Technical Data

IG-262E

Dimensions – External	Dimensions – Internal
Width: 90cm	Width: 87cm
Depth: 85cm	Depth: 82cm
Hight: 110cm	Hight: 107cm
Material	Opening System
Body: SAE 1020	Manual operation
Door: SAE 1020	Front loading
Frames: SAE 1020	1 door, side open
Brackets: SAE 1020	Torque special locking system
Fan: Rubber, Sponge and Plastic	RF shielding doors
Gaskets: Rubber, Sponge and Plastic	
Electric system	Air vents
220 VAC max 16 Amp	2XEMI shielded honeycomb 260X260
4 outlet power strip 220 VAC	4X AC fan 80x80 - 40 CFM, magnetic - bearing, silence
External power cable 220 VAC + plug	
100VDC filter 20amp with easy to use plug in.	
Interrail lighting	
IO's plate	Internal RF absorber
Filtered SMA x4	24 db , internal surfaces covering with RF absorber foam
Attenuation level	Quality
0.1GHz – 1.0GHz > 120dB	Testing according to MIL-STD 285
1.0GHz – 3.0GHz > 120dB	A C.O.A will be attached to each box.
3.0GHz – 6.0GHz > 120dB	Final Attenuation level will set as per as the weak chosen connector
	Warranty – one year from delivering



IG-262E



Technical Drawing

